



## Ultra flexible 0.05 Silicone Wire



### PRODUCT DESCRIPTION

Rated temperature: -60°C~+200°C

Rated voltage: 600V

Reference standard: UL758, UL1581, CSAC22.2 No.21.0

Solid or stranded, tinned copper conductor 32~10AWG

Silicone insulation, compliance with RoHS environmental standard

Passes UL VW-1, CSA FT1/FT2 flame test

Uniform insulation thickness to ensure easy stripping and cutting  
for general purpose internal wiring of appliance



### 印字内容 MARKING (Refer)

200°C 600V

### 产品结构 CONSTRUCTION

规格 AWG	构造 CONSTRUCTION (No./mm)	外径 DLA (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)	包装方式 PACKING (M)
32	11/0.05	0.24	0.40	0.65	2000M
30	28/0.05	0.30	0.45	0.80	1500M
28	40/0.05	0.36	0.38	1.20	400M
26	76/0.05	0.46	0.55	1.50	400M
24	101/0.05	0.61	0.55	1.60	400M
22	153/0.05	0.72	0.49	1.70	400M
20	250/0.05	0.92	0.44	1.80	400M
18	382/0.05	1.13	0.59	2.30	200M
16	636/0.05	1.47	0.77	3.00	200M
14	1018/0.05	1.85	0.83	3.50	200M
12	1710/0.05	2.48	1.05	4.50	100M
10	1070/0.05	3.35	1.30	5.50	100M