



Ultra flexible 0.08 Silicone Wire



PRODUCT DESCRIPTION

Rated temperature: -60°C~+200°C

Rated voltage: 600V

Reference standard: UL758, UL1581, CSAC22.2 No.21.0

Solid or stranded, tinned copper conductor 30~2AWG

Silicone insulation, compliance with RoHS environmental standard

Passes UL VW-1, CSA FT1/FT2 flame test

Uniform insulation thickness to ensure easy stripping and cutting
for general purpose internal wiring of appliance



印字内容 MARKING (Refer)

200°C 600V

产品结构 CONSTRUCTION

规格 AWG	构造 CONSTRUCTION (No./mm)	外径 DLA (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)	包装方式 PACKING (M)
30	11/0.08	0.30	0.55	0.80	1500M
28	16/0.08	0.36	0.38	1.20	400M
26	30/0.08	0.46	0.55	1.50	400M
24	40/0.08	0.61	0.55	1.60	400M
22	600/0.08	0.72	0.49	1.70	400M
20	100/0.08	0.92	0.44	1.80	400M
18	150/0.08	1.13	0.59	2.30	200M
16	252/0.08	1.47	0.77	3.00	200M
14	480/0.08	1.85	0.83	3.50	200M
13	500/0.08	2.00	1.00	4.00	200M
12	680/0.08	2.41	1.05	4.50	200M
11	750/0.08	2.53	1.20	5.00	100M
10	1050/0.08	2.90	1.30	5.50	100M
8	1650/0.08	3.50	1.50	6.50	100M
7	2400/0.08	4.50	1.35	7.20	50M
6	3200/0.08	5.20	1.65	8.50	50M
4	5000/0.08	7.20	2.40	12.0	50M
3	7000/0.08	7.73	2.15	12.0	50M
2	10000/0.08	9.24	1.88	13.0	50M