



## UL style 1015 连接线Hook-up wire

### 产品说明

额定温度：105℃  
额定电压：600V  
参考标准：UL758,UL1581,CSA C22.2 No210.0  
导体使用单支或绞合30~2AWG镀锡或裸铜  
PVC绝缘，符合RoHS环保标准  
通过UL VW-1, CAS FT1/FT2阻燃测试  
绝缘厚度均匀，易裁线，易剥皮  
用于一般电子、电品设备内部接线

### PRODUCT DESCRIPTION

Rated temperature: 105℃  
Rated voltage: 600V  
Reference standard: UL758, UL1581, CSAC22.2 No.21.0  
Solid or stranded, tinned or bare copper conductor 30~2AWG  
PVC insulation, compliance with RoHS environmental standard  
Passes UL VW-1, CSA FT1/FT2 flame test  
Uniform insulation thickness to esure easy stripping and cutting  
for general purpose internal wiring of appliance



### 印字内容 MARKING (Refer)

E336285 AWM 1015 xxAWG VW-1 105℃ 600V AWM IA 105℃ 600V FT1 ZHONGZHENG-LF-

### 产品结构 CONSTRUCTION

规格 AWG	构造 CONSTRUCTION (No./mm)	外径 DLA (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)	最大导体电阻 MAX.COND. RESISTANCE ( $\Omega$ /km 20℃,DC)	包装方式 PACKING (M/FT)
26	1/0.404	0.40	0.80	2.00	143	610M/2KFT
	7/0.16	0.48	0.81	2.10	150	
24	1/0.511	0.51	0.80	2.10	89.3	610M/2KFT
	11/0.16	0.61	0.81	2.30	94.2	
22	1/0.643	0.64	0.80	2.30	56.4	610M/2KFT
	17/0.16	0.76	0.81	2.40	59.4	
20	1/0.813	0.81	0.80	2.40	35.2	610M/2KFT
	26/0.16	0.94	0.81	2.60	36.7	
18	1/1.024	1.02	0.82	2.70	22.2	610M/2KFT
	41/0.16	1.18	0.81	2.80	23.2	
16	1/1.29	1.29	0.81	2.90	14.0	305M/1KFT
	26/0.254	1.49	0.81	3.10	14.6	
14	1/1.6	1.60	0.80	3.20	8.78	305M/1KFT
	41/0.254	1.88	0.81	3.50	8.96	
12	65/0.254	2.36	0.82	4.00	5.64	305M/1KFT
10	7/15/0.254	3.42	0.82	5.10	3.54	305M/1KFT