



UL style 1061 连接线Hook-up wire

产品说明

额定温度: 80°C
 额定电压: 300V
 参考标准: UL758,UL1581,CSA C22.2 No210.0
 导体使用单支或绞合30~14AWG镀锡或裸铜
 SR-PVC绝缘, 符合RoHS环保标准
 通过UL VW-1, CAS FT1/FT2阻燃测试
 绝缘厚度均匀, 易裁线, 易剥皮
 用于一般电子、电品设备内部接线

PRODUCT DESCRIPTION

Rated temperature: 80°C
 Rated voltage: 300V
 Reference standard: UL758, UL1581, CSAC22.2 No.21.0
 Solid or stranded, tinned or bare copper conductor 30~14AWG
 SR-PVC insulation, compliance with RoHS environmental standard
 Passes UL VW-1, CSA FT1/FT2 flame test
 Uniform insulation thickness to ensure easy stripping and cutting
 for general purpose internal wiring of appliance



印字内容 MARKING (Refer)

E336285 AWM 1061 xxAWG VW-1 80°C 300V AWM IA 80°C 300V FT1 ZHONGZHENG-LF-

产品结构 CONSTRUCTION

规格 AWG	构造 CONSTRUCTION (No./mm)	外径 DIA (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)	最大导体电阻 MAX.COND. RESISTANCE (Ω/km 20°C,DC)	包装方式 PACKING (M/FT)
30	1/0.254	0.25	0.25	0.75	361	610M/2KFT
	7/0.10	0.30	0.25	0.80	381	
28	1/0.32	0.32	0.27	0.85	227	610M/2KFT
	7/0.127	0.38	0.26	0.90	239	
26	1/0.404	0.40	0.25	0.90	143	610M/2KFT
	7/0.16	0.48	0.26	1.00	150	
24	1/0.511	0.51	0.25	1.00	89.3	610M/2KFT
	11/0.16	0.61	0.25	1.10	94.2	
22	1/0.643	0.64	0.25	1.20	56.4	610M/2KFT
	17/0.16	0.76	0.27	1.30	59.4	
20	1/0.813	0.81	0.27	1.40	35.2	610M/2KFT
	26/0.16	0.94	0.27	1.50	36.7	
18	1/1.024	1.02	0.27	1.60	22.2	610M/2KFT
	41/0.16	1.18	0.31	1.80	23.2	
16	1/1.29	1.29	0.25	1.80	14.0	305M/1KFT
	26/0.254	1.49	0.31	2.10	14.6	
14	1/1.6	1.60	0.40	2.50	8.78	305M/1KFT
	41/0.254	1.88	0.41	2.70	8.96	