



UL style 1430 连接线Hook-up wire 交联PVC线 Irradiated PVC insulation Wire

产品说明

PRODUCT DESCRIPTION

额定温度: 105°C
 额定电压: 300V
 参考标准: UL758,UL1581,CSA C22.2 No210.0
 导体使用单支或绞合32~16AWG镀锡或裸铜
 XL-PVC绝缘, 符合RoHS环保标准
 通过UL VW-1, CAS FT1/FT2阻燃测试
 绝缘厚度均匀, 易裁线, 易剥皮
 用于一般电子、电品设备内部接线

Rated temperature: 105°C
 Rated voltage: 300V
 Reference standard: UL758, UL1581, CSAC22.2 No.21.0
 Solid or stranded, tinned or bare copper conductor 32~16AWG
 XL-PVC insulation, compliance with RoHS environmental standard
 Passes UL VW-1, CSA FT1/FT2 flame test
 Uniform insulation thickness to esure easy stripping and cutting
 for general purpose internal wiring of appliance



印字内容 MARKING (Refer)

E336285 AWM 1430 xxAWG VW-1 105°C 300V AWM IA 105°C 300V Ft1 ZHONGZHENG-LF-

产品结构 CONSTRUCTION

规格 AWG	构造 CONSTRUCTION (No./mm)	外径 DLA (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)	最大导体电阻 MAX.COND. RESISTANCE (Ω/km 20°C,DC)	包装方式 PACKING (M/FT)
30	1/0.254	0.25	0.40	1.05	361	610M/2KFT
	7/0.10	0.30	0.40	1.10	381	
28	1/0.32	0.32	0.39	1.10	227	610M/2KFT
	7/0.127	0.38	0.41	1.20	239	
26	1/0.404	0.40	0.43	1.25	143	610M/2KFT
	7/0.16	0.48	0.41	1.30	150	
24	1/0.511	0.51	0.42	1.35	89.3	610M/2KFT
	11/0.16	0.61	0.40	1.40	94.2	
22	1/0.643	0.64	0.43	1.50	56.4	610M/2KFT
	17/0.16	0.76	0.42	1.60	59.4	
20	1/0.813	0.81	0.42	1.65	35.2	610M/2KFT
	26/0.16	0.94	0.43	1.80	36.7	
18	1/1.024	1.02	0.41	1.85	22.2	610M/2KFT
	41/0.16	1.18	0.47	2.10	23.2	
16	1/1.29	1.29	0.46	2.20	14.0	610M/2KFT
	26/0.254	1.49	0.46	2.40	14.6	