



UL style 2468 连接线 Flat ribbon cable

产品说明

额定温度: 80℃
额定电压: 300V
参考标准: UL758,UL1581,CSA C22.2 No210.0
导体使用单支或绞合32~16AWG镀锡或裸铜
PVC绝缘, 符合RoHS环保标准
通过UL VW-1, CAS FT1/FT2阻燃测试
绝缘厚度均匀, 易裁线, 易剥皮
用于一般电子、电品设备内部接线

PRODUCT DESCRIPTION

Rated temperature: 80℃
Rated voltage: 300V
Reference standard: UL758, UL1581, CSAC22.2 No.21.0
Solid or stranded, tinned or bare copper conductor 32~16AWG
PVC insulation, compliance with RoHS environmental standard
Passes UL VW-1, CSA FT1/FT2 flame test
Uniform insulation thickness to ensure easy stripping and cutting
for general purpose internal wiring of appliance



印字内容 MARKING (Refer)

E336285 AWM 2468 xxAWG VW-1 80℃ 300V AWM IA 80℃ 300V FT1 ZHONGZHENG-LF-

产品结构 CONSTRUCTION

规格 AWG	间距 PITCH	构造 CONSTRUCTION (No./mm)	外径 DLA (mm)	芯数 Cores (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)	最大导体电阻 MAX.COND. RESISTANCE (Ω/km 20℃,DC)	包装方式 PACKING (M/FT)
28	1.25	7/0.127	0.38	2	0.44	1.25×2.50	239	610M/2KFT
26	1.50	7/0.16	0.48	2	0.44	1.35×2.85	150	610M/2KFT
24	2.00	11/0.16	0.61	2	0.44	1.35×3.35	94.2	610M/2KFT
22	2.50	17/0.16	0.76	2	0.44	1.35×6.35	59.4	610M/2KFT
20	1.60	26/0.16	0.94	2	0.42	1.45×3.05	36.7	610M/2KFT
18	2.00	41/0.16	1.18	2	0.43	1.45×3.45	22.2	305M/1KFT
16	2.50	26/0.16	1.49	2	0.43	1.45×3.95	36.7	610M/2KFT
14	2.80	41/0.254	1.88	2	0.47	1.70×3.50	150	610M/2KFT