



UL style 2651 连接线 Flat cable

产品说明

额定温度: 105°C
 额定电压: 300V
 参考标准: UL758,UL1581,CSA C22.2 No210.0
 导体使用单支或绞合36~14AWG镀锡或裸铜
 PVC绝缘, 符合RoHS环保标准
 通过UL VW-1, CAS FT1/FT2阻燃测试
 绝缘厚度均匀, 易裁线, 易剥皮
 用于一般电子、电品设备内部接线

PRODUCT DESCRIPTION

Rated temperature: 105°C
 Rated voltage: 300V
 Reference standard: UL758, UL1581, CSAC22.2 No.21.0
 Solid or stranded, tinned or bare copper conductor 36~14AWG
 PVC insulation, compliance with RoHS environmental standard
 Passes UL VW-1, CSA FT1/FT2 flame test
 Uniform insulation thickness to ensure easy stripping and cutting
 for general purpose internal wiring of appliance



印字内容 MARKING (Refer)

E336285 AWM 2651 xxAWG VW-1 105°C 300V AWM IA 105°C 300V FT1 ZHONGZHENG-LF-

产品结构 CONSTRUCTION

规格 AWG	间距 PITCH	构造 CONSTRUCTION (No./mm)	外径 DLA (mm)	芯数 Cores (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)	最大导体电阻 MAX.COND. RESISTANCE (Ω/km 20°C,DC)	包装方式 PACKING (M/FT)
28	1.25	7/0.127	0.38	2	0.27	0.92×2.54	239	610M/2KFT
	1.25	7/0.127	0.38	3	0.27	0.92×3.81	239	610M/2KFT
	1.25	7/0.127	0.38	4	0.27	0.92×5.08	239	610M/2KFT
	1.25	7/0.127	0.38	5	0.27	0.92×6.35	239	610M/2KFT
26	1.50	7/0.16	0.48	2	0.44	1.35×2.85	150	610M/2KFT
	1.50	7/0.16	0.48	3	0.44	1.35×4.35	150	610M/2KFT
	1.50	7/0.16	0.48	4	0.44	1.35×5.85	150	610M/2KFT
	1.50	7/0.16	0.48	5	0.44	1.35×7.35	150	610M/2KFT