



UL style 3386 连接线Hook-up wire

产品说明

额定温度：105℃
额定电压：600V
参考标准：UL758,UL1581,CSA C22.2 No210.0
导体使用单支或绞合32~10AWG镀锡或裸铜
XL-PE绝缘，符合RoHS环保标准
通过UL VW-1, CAS FT1/FT2阻燃测试
绝缘厚度均匀，易裁线，易剥皮
用于一般电子、电品设备内部接线

PRODUCT DESCRIPTION

Rated temperature: 105℃
Rated voltage: 600V
Reference standard: UL758, UL1581, CSAC22.2 No.21.0
Solid or stranded, tinned or bare copper conductor 32~10AWG
XL-PE insulation, compliance with RoHS environmental standard
Passes UL VW-1, CSA FT1/FT2 flame test
Uniform insulation thickness to ensure easy stripping and cutting
for general purpose internal wiring of appliance



印字内容 MARKING (Refer)

E336285 AWM 3385 xxAWG VW-1 105℃ 600V AWM IA 105℃ 600V FT1 ZHONGZHENG-LF- -HF-

产品结构 CONSTRUCTION

规格 AWG	构造 CONSTRUCTION (No./mm)	外径 DLA (mm)	厚度 THICKNESS (mm)	外径 O.D. (mm)	最大导体电阻 MAX.COND. RESISTANCE (Ω/km 20℃,DC)	包装方式 PACKING (M/FT)
32	1/0.20	0.20	0.40	1.00	563	610M/2KFT
	7/0.08	0.24	0.40	1.05	588	
30	1/0.254	0.25	0.40	1.05	361	610M/2KFT
	7/0.10	0.30	0.40	1.10	381	
28	1/0.32	0.32	0.39	1.10	227	610M/2KFT
	7/0.127	0.38	0.41	1.20	239	
26	1/0.404	0.40	0.43	1.25	143	610M/2KFT
	7/0.16	0.48	0.41	1.30	150	
24	1/0.511	0.51	0.42	1.35	89.3	610M/2KFT
	11/0.16	0.61	0.40	1.40	94.2	
22	1/0.643	0.64	0.43	1.50	56.4	610M/2KFT
	17/0.16	0.76	0.42	1.60	59.4	
20	1/0.813	0.81	0.42	1.65	35.2	610M/2KFT
	26/0.16	0.94	0.43	1.80	36.7	
18	1/1.024	1.02	0.41	1.85	22.2	610M/2KFT
	41/0.16	1.18	0.47	2.10	23.2	
16	1/1.29	1.29	0.46	2.20	14.0	610M/2KFT
	26/0.254	1.49	0.46	2.40	14.6	